

Current Journal of Applied Science and Technology

32(6): 1-8, 2019; Article no.CJAST.47110 ISSN: 2457-1024 (Past name: British Journal of Applied Science & Technology, Past ISSN: 2231-0843, NLM ID: 101664541)

Economic Analysis of Rice Cultivation System under Different Establishment Methods

Rakesh Kumar^{1*}, Vikas Paradkar² and Shashank Singh³

¹Farm Machinery and Power Engineering, Sam Higginbottom University of Agriculture, Technology and Sciences, Allahabad, Uttar Pradesh, India. ²Farm Machinery and Power Engineering, IIT Kharagpur, India. ³Sr. Faculty Institute of Livihood Research and Training, Bhopal, Madhya Pradesh, India.

Authors' contributions

This work was carried out in collaboration between all authors. All authors read and approved the final manuscript.

Article Information

DOI: 10.9734/CJAST/2019/v32i630034 <u>Editor(s)</u>: (1) Dr. Teresa De Pilli, Assistant Professor, Department of Science of Agriculture of Food of Environment (SAFE), University of Foggia, Via Napoli, Italy. <u>Reviewers:</u> (1) Bilal Ahmad Lone, Sher-e-Kashmir University of Agricultural Sciences and Technology, India. (2) Venkata Sanyasi Seshendra Kumar Karri, GITAM University, India. (3) A. Ashok Kumar, Dr. NTR College of Agricultural Engineering, Acharya NG Ranga Agricultural University, India. Complete Peer review History: <u>http://www.sdiarticle3.com/review-history/47110</u>

> Received 03 November 2018 Accepted 28 January 2019 Published 15 February 2019

Original Research Article

ABSTRACT

Energy utilization efficiency depends on different factor of cropping systems such as physiochemical properties of soil, land preparing operation, plant protection, fertilizer application, threshing, harvesting operation and grain and straw yield. India is developing county and rice crops are one of the most energy intensive crop and its major component are irrigation, land development (tillage), FYM (Farmyard manure) and fertilizers. The importance of Mechanization in cultivation system involves higher input cost but at the same time, it can reduce operation cost of cultivation, increases grain yield and can reduce operational time. Cost of cultivation of rice in different treatment was calculated by adding the cost of all input parameter such as seeds, fertilizers, pesticides, fuel, and labourer. Grain output was observed considerably higher in mechanized transplanting seedling compare to direct sowing. Direct sowing and zero till mechanical transplanting seedling of rice in a standing water table. The grain yield in mechanical transplanting varied from 29.5 to 32.6 q/h where as in direct sowing treatment 31.2 to 32.1 q/ha.

Keywords: Rice transplanting; zero till drill; energy utilization etc.

1. INTRODUCTION

The cost of energy in agriculture have increased day by day and it is one of the most important input parameter in the practice of crop cultivation and it is required at each step of crop production from initial phase (tillage) to final (harvesting). In each operation of crop production there is application of input that depends on energy base fossil fuel (mechanical machinery) consumption emits carbon-di-oxide which and other greenhouse gases. Energy utilization efficiency depends on different factor of cropping systems such as physiochemical properties of soil, land preparing operation, plant protection, fertilizer application, harvesting, threshing operation and grain and straw yield [1]. India is developing county and here the rate of energy consumption is rising day by day with the involvement of new technology in the field of agriculture [2]. However, there are advantages of the use of new technology and machineries in agriculture that can reduce the energy need by 18-83% in tillage operation with different cultivation system [3].

Rice crops is one of the most energy intensive crop and its major component are irrigation, land development (tillage), FYM (Farmyard manure) and fertilizers. In India per capita energy availability is 1.84 kW/ha (Department of agriculture cooperation and farmers welfare) and in Haryana is 2 kw/ha. Therefore, there is a need to classify energy-efficient rice cultivation system, [4]. The cost of cultivation is equally important for developing county like India where resources are limited and farmers are poor. Initial cost input for rice cultivation is higher and its output from rice cultivation is a major concern among the rice cultivators [5]. The importance of Mechanization in cultivation system involves higher input cost but at the same time it can reduces operation cost of cultivation, increase in grain yield and can reduce operational time [6]. Therefore, there is a need to analyse an efficient rice cultivation system in terms of benefit cost ratio. The present study was taken on rice cultivation with the objective to analyse economics and energy efficiency in the state of Haryana.

2. METHODOLOGY

2.1 Experimantal Site

2.1.1 Transplanting/sowing field preparation according to treatments

The study was conducted in flatland of Agricultural Engineering farms of the Choudhary Charan Singh Agricultural University at Hisar, Haryana State of India. The data were obtained from field experiments conducted in Kharif seasons.

Treatments	Methods	Description	Plot size(m ²)		
T ₁	Direct seeded rice (vattar)	One Plough + harrow + planking (with cultivator) + sowing by drill	46.75		
T ₂	Zero till-direct seeded rice without residues				
T ₃	Zero till-direct seeded rice with residues/Sesbania	Sowing by drill + residues (no tillage)	46.75		
T ₄	Zero till-mechanical transplanting	Self propelled rice transplanting (no tillage in standing water)	46.75		
T ₅	Unpuddle-mechanical transplanting	One Plough + harrow + planking (with cultivator) + Self propelled rice transplanting (standing water)	46.75		
T ₆	Puddle-mechanical transplanting	······································			
T ₇	Puddle-manual transplanting	One Plough + harrow + planking (with cultivator) + puddling (with rotavator) + manual planting	46.75		

Table 1. Transplanting/sowing field preparation according to treatments

Experimental plan was conducted for analysis of yield for different rice cultivation practices. Seven treatment was selected as described in Table 1. These systems involved direct sowing rice (vattar) (T_1), Zero till-direct sowing rice without residues (T_2), Zero till-direct seeded rice with residues/Sesbania (T_3), Zero till-mechanical transplanting (T_4), Unpuddle-mechanical transplanting (T_5), Puddle-mechanical transplanting (T_7).

The University is situated 30 km away from Kurukshetra city at latitude 29°51' N, longitude 76°41' E and altitude 241 meters above mean sea level. The field was selected for the study and it was uniform fertile. A composite soil sample from 0-30 cm soil depth was taken randomly at three places from the field before layout of experiment. The sample were mixed thoroughly, dried and were subjected to mechanical and chemical analysis. The physio-chemical analysis of the soil is presented in Table 2.

Table 2. Physio-chemical analysis of the soil of the experimental field

Soil components	Content (%)
Sand	32.00
Silt	38.00
Clay	30.00
Soil pH (1:2)	8.20
Organic carbon (%)	0.32
EC (ds/m)	0.27

2.2 Experimental Management Practices

Seven different experimental management practices were followed and different inputs were used in seven rice cultivation systems which are summarized in Table 1. Plot size for each treatment was 46.75 m^2 . In Direct sowing rice

land was prepared with single Mould Board Plough, one harrow, planking (with cultivator) operation were operated 10-15 days before sowing and seed was sown by seed drill. In T_2 treatment the seeds were sown with drill directly in the soil without any tillage operation. This treatment is zero till drill but in this treatment field was selected with no residue. In T₃ treatment which was similar to the T₂ treatment but the field was selected with residue for conserving moisture. In T₄ to T₇ treatments were done in standing water field and seedlings were grown for this treatment and transplanted into the field. For conventional and mechanized transplanting average 25 day-old seedlings with two to three seedlings per hill were transplanted at a spacing of 20 × 15 cm and 24 × 15 cm, respectively. Seedlings were grown on raised bed of 1 × 8 m area and 10 cm height. The seedbeds were sprinkled with water manually at regular interval. Taking care with transplanting seedlings, it was transplanted within 30 minutes after uprooting them from the nursery to avoid wilting and reduce transplanting shock. Transplanting in mechanized system was done by using 8-row self-propelled paddy transplanter.

In T₄ treatment no tillage operation was carried out and seedlings were transplanted with mechanical transplanter. And tillage operation is carried out in T₅. T₆ and T₇ treatments. Seedlings were transplanted mechanically in T₅ and T₆ treatment and manual transplanting was done in T₇ treatment.

2.3 Energy Balance

Energy balance was calculated using the different equivalents of cultivation practices and outputs. Energy equivalents of the machines which was commonly available [7] in India (Table 3).

S.No.	Particulars	Energy equivalent(MJ/h)		
1	Power tiller	6.693		
2	Rice Transplanter	5.02		
3	Power weeder	0.251		
5	Knapsack sprayer	0.258		
6	Power operated sprayer	1.703		
7	Reaper	1.96		
8	Pedal operated thresher	1.01		
9	Power thresher	16.2		

Table 3. Energy equivalent of machineries for India

2.4 Economic Analysis

Cost of cultivation of rice in different treatment was calculated by adding the cost of all input parameter such as seeds, fertilizers, pesticides, fuel, labourers, etc. and cost of operation machinery [4]. Costs of fertilizers, FYM, seeds and pesticides were calculated on the basis of the available market price in the corresponding years. Manual cost was used to estimate on the basis of available rate on the Government of India (Ministry of Labour and Employment). The cost of operation of the machinery was computed on hourly basis after including the cost of machine, depreciation of the machine, machine Life and rate of interest. Available fuel rates (petrol and diesel) were obtained from the locally available petrol pump. Gross returns were calculated on the basis of support price, price of rice announced by Government of India for kharif season of 2011.

Net returns (Rs/ha) were worked out by subtracting the total cost of cultivation of each treatment from the gross income of respective treatment. Benefit: Cost (B:C) ratio was calculated to ascertain economic viability of the treatment by using the following formula:

Net return = (Product cost + Byproduct cost) - Input cost

Benefit-cost ratio =Total output cost/Total Input cost

3. RESULTS AND DISCUSSION

3.1 Energy Input

Energy required for cultivation of the crop in seven cultivation systems are presented in Table 5. Significantly high amount of energy required in Haryana for irrigation which was 30 Rs/hr. Land preparation consumed 1468 Rs/ha for flat land without standing water table whereas 3033 Rs/ha for standing water table field. Consumption of considerably more energy for fertilizers and manure than that of other cultural systems [8,6,9,10].

The cost analysis of different establishment methods were analyzed and given in Table 4. The comparative economics of different establishment methods were analyzed and reported in Table 4. Cost of operation was maximum (Rs. 8033) under treatment T_7 followed by T_6 then T_5 , T_1 then T_4 and minimum (Rs. 629) was in treatment T_2 and T_3 . It is clear from the table 4 maximum cost of operation was under manual method (8033 Rs/ha). It was minimum under treatment T_3 (Rs. 62/ha) because no tillage operation was performed in this treatment. The total cost of production was also maximum under treatments followed by T_6 , T_5 , T_4 , T_1 and minimum was under treatment T_2 and T_3 .

Tillage operations used great amount of energy for land preparation. The energy requirement was negligible in zero till systems for tillage operation, which were major advantages over the conventional tillage. Direct sowing (Rs 16491) and manual transplanting of seedling (Rs 25388) kind of treatment required higher energy input than compare to zero till treatment (Rs 14974) because it used energy for tillage, transplanting, and manpower to rise mat-type seedlings. On comparing other side direct sowing can reduced the energy input as compared to mechanical transplanting because there was no need to raise seedling. Land preparation, transplanting or harvesting, fertilizer, sowing, and FYM applications together accounted for great amount of energy input.

3.2 Crop Performance under Different Methods of Rice Establishment

The plant height under different methods of rice establishment was given in Fig 1. The plant height was recorded at the time interval of 7, 14, 21, 35, 42 and 49 DAS/DAP. During these time interval the maximum plant height was obtained in 4.63, 12.7, 21.86, 29.97, 35.83 and 44 cm respectively. The minimum height of plant was obtained 4.04, 11.25, 18.73, 28.33, 34.42, and 42.60 cm with the $T_1(7)$, T_2 (14 & 21), T_5 (35), T_4 (42) and T_4 (49) day respectively. The overall plant height was maximum (126.59cm) under T_6 and minimum (121.00 cm) was obtained in T_2 respectively.

3.3 Crop Yield under Different Methods of Rice Establishment

The effect of various treatments on crop yield was days to crop maturity, number of grain in a panicle, panicle length, number tillers/m², straw and crop yield (grain) were recorded at time of crop harvesting and results are reported in Table 5. the plant height at crop maturity in mechanical transplanting varied from 121.8 to 126.5 cm whereas in direct sowing the plant height at crop maturity was in the range 121 to 123.5 cm and

Kumar et al.; CJAST, 32(6): 1-8, 2019; Article no.CJAST.47110

Sr. No.	Particulars	T ₁	T ₂	T ₃	T_4	T₅	T ₆	T ₇
Input cos	st (Rs/ha)							
1	Preparatory tillage	1468	-	-	-	1468	3033	3033
	a. Harrowing @738 Rs/ha							
	 b. Planker along with cultivator @ 730 Rs/ha 							
	c. Rotavator two operation @ 1565 rs/ha							
2	Sowing/transplanting	629	629	629	1372	1372	1372	5000
	Total operation cost	2097	629	629	1372	2840	4405	8033
3	Seed 20 kg/ha @ 40 Rs/kg	800	800	800	800	800	800	800
4	Nursery raising (6man/day/ha)	-	-	-	1014	1014	1014	1014
5	seed treatment emisalt @ 250 Rs/ha	250	250	250	250	250	250	250
6	Bund making	250	250	250	250	250	250	250
7	Fertilizers	1575	1575	1575	1575	1575	1575	1575
	a. urea Rs 250/- 50 kg bag							
	b. single superphosphate Rs 250/- 50 kg bag							
	c. muriate of potash @ Rs 250/- 50 kg bag							
8	Irrigations30 Rs/ha	5700	5700	5700	8000	8000	8000	8000
9	Weeding 4man/day/ha	676	676	676	676	676	200	200
10	Plant protectionBrown spot, steam root cutter, indosulphan @2 kg/ha	1500	1500	1500	1500	1500	1500	1500
11	Harvesting/ threshing	2600	2600	2600	2600	2600	2600	2600
	Total cost	15936	14468	14468	18525	19993	20882	2451
13	Interest (3.5%) on total cost	558	506	506	648	700	731	878
14	Total input cost	16494	14974	14974	19173	20693	21613	2538
15	Rental value of land	37500	37500	37500	37500	37500	37500	3750

Table 4. Economics of rice cultivation as influenced by different crop establishment techniques





Fig. 1. Plant growth with time interval for different treatment

manual transplanting it was found 126.4 cm. Duration of the crop maturity in all treatment was nearly same and it was 144-145 days. The number of effective tillers per square meter was found in the range of 218 to 220 when rice crop was transplanted with mechanical transplanter and sown with direct sowing method. In manual transplanting number of effective tillers per square meter were 221. The numbers of grains per panicle in mechanical transplanting varied from 73.3 to 78.7 whereas in direct sowing numbers of grains per panicle were 73.5 to 78.33 and in manual transplanting it was observed 79.55.

Grain output was also considerably higher in mechanized transplanting seedling compare to direct sowing. Direct sowing and zero till mechanical transplanting methods produced the low grain yield because of poor crop growth. Low productivity was observed in zero till mechanized transplanting the reason may be due to missing hills of the seedlings while transplanting with the machine or soil bed not prepared well in standing water. Further, production of straw or biomass was more in zero till direct sowing treatment with stubble leading to a higher straw production compare to other cultivation treatment. The grain yield in mechanical transplanting varied from 29.5 to 32.6 g/h where as in direct sowing treatment 31.2 to 32.1 q/ha. The maximum production kg/ha per hectare was from under treatment T_6 followed by T_7 and minimum was under treatment T₄.The gross return (69578 Rs/ha) was maximum under treatment T_6 followed by T_5 and T_2 and minimum was under treatment T₄.Net return (Rs. 63367/ha) was maximum under treatment T_3 followed by T_2 . The benefit cost ratio was maximum (1.3) under treatment T₂ whereas in other treatment it varied from 1.27 to 1.30.

Treatments	Days to crop maturity	Panicle length (cm)	No. of effective tillers/m ² at harvest	No. of grains/panicle	Grain yield (kg/ha)	Straw (kg/Ha)
T ₁	144	23.26	220	76.66	3178	4225.0
T ₂	144	23.26	220	73.52	3129	4693.5
T ₃	144	23.77	221	78.33	3219	4828.5
T ₄	145	22.56	218	73.30	2975	3834.3
T₅	145	23.55	220	76.61	3194	4299.6
T ₆	145	23.98	220	78.77	3267	4304.2
T ₇	145	24.34	221	79.55	3202	4076.5

Table 5. Crop yield under different methods of rice establishment





3.4 Economics

Zero till direct sowing (T2 and T3) was costeffective energy saving rice cultivation treatment. Cost of cultivation in all mechanized treatment was considerably less as compare to the manual transplanting treatment. Total cost of cultivation in treatment T2 and T3 was lower and the amount was 52474 Rs/ha and the cost of cultivation in transplanting treatment was higher shown in Fig. 2. The cost of manual transplanting was highest among all the treatment and that was 62888 Rs/ ha. Above result suggest the requirements for mechanization of rice production in the Northern region of India. Advantages of mechanized system had requirement of labour was low as compare to manual transplanting, which effect cost of cultivation.

Economic return of the crop cultivation was directly related to the yield (q/ha) of rice in different cultivation treatment. The benefit to cost ratio (B:C) of the T3 treatment was considerably higher than all other treatment and the lowest benefit to cost ratio was observed in manual transplanting.

4. CONCLUSION

Following conclusion from the above study:

1. Cost of manual transplanting was INR 62888 per Ha and it was observed highest compared with other treatments.

- 2. The numbers of grains per panicle in mechanical transplanting varied from 73.3 to 78.7 whereas in direct sowing numbers of grains per panicle were 73.5 to 78.33 and in manual transplanting it was observed 79.55.
- 3. The benefit to cost ratio for T3 treatment was 1.30 and it was highest as compared to other treatment.
- 4. The benefit cost ratio for treatment T_2 and T_3 were obtained highest 1.21 and 1.25 respectively. However T_7 and T_4 were obtained lowest 1.08 and 1.16 respectively

COMPETING INTERESTS

Authors have declared that no competing interests exist.

REFERENCES

- 1. Yogeswari D, Porpavai S. Effect of crop establishment methods and irrigation scheduling on growth and yield of rice. IJCS. 2018;6(4):32-35.
- 2. Das FC. Status and prospects of mechanisation in rice, rice knowledge management portal; 2012. Available:http://www.rkmp.co.in

[Accessed online on 14 September, 2013]

- Sørensen CG, Nielsen V. Operational analyses and model comparison of machinery systems for reduced tillage. Biosyst Eng. 2005;92:143–55.
- 4. Sartori L, Basso B, Bertocco M, Oliviero G. Energy use and economic evaluation of a

three year crop rotation for conservation and organic farming in NE Italy. Biosyst Eng. 2005;91:245–56.

- Das A, Patel DP, Munda GC, Ramkrushna GI, Kumar M, Ngachan SV. Improving productivity, water and energy use efficiency in lowland rice (*Oryza sativa*) through appropriate establishment methods and nutrient management practices in themid-altitude of North-East India. Exp Agric. 2014;50:353–7.
- Mandal KG, Saha KP, Ghosh PK, Hati KM, Bandyopadhyay KK. Bioenergy and economic analysis of soybean-based crop production systems in central India. Biosyst Eng. 2002;23:337–45.

- Mittal JP, Dhawan KC. Research manual on energy requirements in agricultural sector. New Delhi: ICAR. 1988;20–33.
- 8. Verma UN, Thakur R, Singh MK, Pal SK. Fertilizer energy management in cropping systems. Fertilizer News. 1995;19–25.
- Salami P, Ahmadi H, Keyhani A. Energy use and economic analysis of strawberry production in Sanandaj zone of Iran. Biotechnol Agron Soc Environ. 2010;14: 653–8.
- Sørensena CG, Halbergb N, Oudshoorna FW, Petersenc BM, Dalgaardd R. Energy inputs and GHG emissions of tillage systems. Biosyst Eng; 2014. Available:http://dx.doi.org/10.1016/j.

© 2019 Kumar et al.; This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Peer-review history: The peer review history for this paper can be accessed here: http://www.sdiarticle3.com/review-history/47110